

TECO #4186 - Misty Waters Lot Elevations

100-year flood plain elevation is 1639.00 and all elevations are NGVD-29

Block	Lot	Lot Elevation	Bottom of Footing Elevation	Approximate Allowed Depth of Basement or Crawl Space (ft)
1	3	1642.48	1635.00	6.15
1	4	1643.23	1635.00	6.90
1	5	1642.93	1635.00	6.60
1	6	1642.50	1635.00	6.17
1	7	1641.88	1635.00	5.55
1	8	1641.75	1635.00	5.42
1	9	1641.69	1635.00	5.36
1	10	1641.83	1635.00	5.50
1	11	1642.43	1635.00	6.10
1	12	1642.92	1635.00	6.59
1	13	1642.79	1635.00	6.46
1	14	1642.48	1635.00	6.15
1	15	1643.34	1635.00	7.01
1	16	1644.02	1635.00	7.69
1	17	1644.50	1635.00	8.17
1	18	1644.02	1635.00	7.69
1	19	1643.65	1635.00	7.32
1	20	1643.45	1635.00	7.12
1	21	1642.96	1635.00	6.63
1	22	1642.60	1635.00	6.27
1	23	1643.21	1635.00	6.88
1	24	1643.96	1635.00	7.63
1	25	1644.39	1635.00	8.06
1	26	1645.10	1635.00	8.77
1	27	1643.96	1635.00	7.63
1	28	1644.05	1635.00	7.72
1	29	1643.44	1635.00	7.11
1	30	1643.31	1635.00	6.98
1	31	1642.17	1635.00	5.84
1	32	1641.61	1635.00	5.28
1	33	1640.92	1635.00	4.59
1	34	1640.78	1635.00	4.45
1	35	1640.76	1635.00	4.43
1	36	1640.54	1635.00	4.21
1	37	1640.80	1635.00	4.47
1	38	1642.13	1635.00	5.80
1	39	1641.77	1635.00	5.44
1	40	1642.70	1635.00	6.37
1	41	1642.98	1635.00	6.65
1	42	1642.68	1635.00	6.35
1	43	1642.25	1635.00	5.92

Note:

- 1.) Elevations are based on topography survey performed on January, 2006 and each lot elevation should be field verified prior to any construction.
- 2.) Elevations are taken from the middle of the building corridor and centered in the middle of the lot.
- 3.) Approximate Allowed Depth of Basement or Crawl Space = Lot Elevation - Bottom of Footing - 1 foot (Thickness of Footing) - 0.33 feet (Thickness of Basement Floor)
- 4.) Round down to the nearest quarter of a foot

TECO #4186 - Misty Waters Lot Elevations

100-year flood plain elevation is 1639.00 and all elevations are NGVD-29

Block	Lot	Lot Elevation	Bottom of Footing Elevation	Approximate Allowed Depth of Basement or Crawl Space (ft)
1	44	1642.42	1635.00	6.09
1	45	1643.30	1635.00	6.97
1	46	1644.26	1635.00	7.93
1	47	1644.07	1635.00	7.74
1	48	1643.54	1635.00	7.21
1	49	1642.06	1635.00	5.73
1	50	1640.95	1635.00	4.62
1	51	1641.76	1635.00	5.43
1	52	1642.96	1635.00	6.63
1	53	1644.07	1635.00	7.74
1	54	1643.18	1635.00	6.85
1	55	1641.63	1635.00	5.30
1	56	1641.76	1635.00	5.43
1	57	1642.42	1635.00	6.09
1	58	1642.71	1635.00	6.38
1	59	1642.41	1635.00	6.08
1	60	1642.45	1635.00	6.12
1	61	1642.59	1635.00	6.26
1	62	1642.14	1635.00	5.81
1	63	1641.92	1635.00	5.59
1	64	1642.42	1635.00	6.09
1	65	1642.72	1635.00	6.39
1	66	1643.04	1635.00	6.71
1	67	1642.91	1635.00	6.58
1	68	1642.37	1635.00	6.04
1	69	1643.62	1635.00	7.29
1	70	1643.88	1635.00	7.55
1	71	1643.74	1635.00	7.41
1	72	1642.89	1635.00	6.56
1	73	1642.36	1635.00	6.03
1	74	1643.20	1635.00	6.87
1	75	1643.45	1635.00	7.12
1	76	1642.83	1635.00	6.50
1	77	1642.49	1635.00	6.16
1	78	1642.82	1635.00	6.49
1	79	1642.62	1635.00	6.29
1	80	1642.52	1635.00	6.19
1	81	1642.71	1635.00	6.38
1	82	1643.09	1635.00	6.76
1	83	1643.94	1635.00	7.61

Note:

- 1.) Elevations are based on topography survey performed on January, 2006 and each lot elevation should be field verified prior to any construction.
- 2.) Elevations are taken from the middle of the building corridor and centered in the middle of the lot.
- 3.) Approximate Allowed Depth of Basement or Crawl Space = Lot Elevation - Bottom of Footing - 1 foot (Thickness of Footing) - 0.33 feet (Thickness of Basement Floor)
- 4.) Round down to the nearest quarter of a foot

TECO #4186 - Misty Waters Lot Elevations

100-year flood plain elevation is 1639.00 and all elevations are NGVD-29

Block	Lot	Lot Elevation	Bottom of Footing Elevation	Approximate Allowed Depth of Basement or Crawl Space (ft)
3	2	1641.28	1635.00	4.95
3	3	1642.52	1635.00	6.19
3	4	1644.14	1635.00	7.81
3	5	1644.11	1635.00	7.78
3	6	1645.08	1635.00	8.75
3	7	1644.40	1635.00	8.07
3	8	1644.07	1635.00	7.74
3	9	1644.31	1635.00	7.98
3	10	1644.27	1635.00	7.94
3	11	1643.17	1635.00	6.84
3	12	1644.07	1635.00	7.74
3	13	1643.20	1635.00	6.87
3	14	1642.27	1635.00	5.94
3	15	1642.16	1635.00	5.83
3	16	1642.69	1635.00	6.36
3	17	1642.85	1635.00	6.52
3	18	1642.36	1635.00	6.03
3	19	1642.23	1635.00	5.90
3	20	1641.98	1635.00	5.65
3	21	1642.35	1635.00	6.02
3	22	1642.16	1635.00	5.83
3	23	1641.97	1635.00	5.64
3	24	1642.39	1635.00	6.06
3	25	1642.68	1635.00	6.35
3	26	1642.94	1635.00	6.61
3	27	1642.34	1635.00	6.01
3	28	1642.26	1635.00	5.93
3	29	1642.26	1635.00	5.93
3	30	1643.11	1635.00	6.78
3	31	1643.60	1635.00	7.27
3	32	1643.21	1635.00	6.88
3	33	1642.09	1635.00	5.76
3	34	1641.83	1635.00	5.50
3	35	1642.45	1635.00	6.12
3	36	1642.05	1635.00	5.72
3	37	1641.43	1635.00	5.10
3	38	1643.62	1635.00	7.29
3	39	1644.99	1635.00	8.66

Note:

- 1.) Elevations are based on topography survey performed on January, 2006 and each lot elevation should be field verified prior to any construction.
- 2.) Elevations are taken from the middle of the building corridor and centered in the middle of the lot.
- 3.) Approximate Allowed Depth of Basement or Crawl Space = Lot Elevation - Bottom of Footing - 1 foot (Thickness of Footing) - 0.33 feet (Thickness of Basement Floor)
- 4.) Round down to the nearest quarter of a foot